

CUSTOM APPLICATION ENGINEERING

Quality Clutches, Brakes, Torque Limiters, and Web Control Systems Designed for You



Nexen's Custom Business Unit (CBU) will adapt and alter any Nexen product to meet your unique motion control, power transmission and power-off brake needs. Whether the application calls for a new unit or simply a modification to an existing unit, Nexen shows you how air-engaged clutches, brakes and torque limiters save time and money by providing the most efficient products in the industry. Our fast design, quotation and delivery response make this an easy, cost-effective option.

Nexen's extensive product line of more than 2500 component and systems for start-stop, disconnect and overload protection demonstrate our commitment to serve any motion control need. Nexen also offers products and systems for web tension applications that ensure proper web process control.

Industries Served

Packaging
Food Processing
Material Handling / Conveyors
Foundry Equipment
Automotive Production Equipment
Commercial Laundry
Wind Turbine

Product Experience

Pneumatically Engaged Brakes
Pneumatically Engaged Clutches
Pneumatically Engaged Torque Limiters
Pneumatically Engaged Clutch-Brakes
Spring-Engaged, Power-Off, Holding Brakes

Application Specialties

Power Transmission Web Process control Motion Control Power-Off, Safety Brakes Wood/Paper Processing, Converting Printing Newspaper Production


Linear Systems
Robotics
Machine Tool
... and many more

Servo Motor Brakes Web Tension Control Brakes Web Tension Control Clutches Web Tension Electronic Controls Web Guides

Custom Clutches, Brakes and Torque Limiters

SAFETY, POWER-OFF BRAKES

Servo Motor Brake modified to fit a NEMA flanged gear reducer




Gantry Robot System

Nexen's CBU re-configured the flanges to mount the brake between a servo motor and a NEMA flanged gear reducer.

RESULT: New brake performs dynamic stopping and holding functions in power-off situations.

HIGH TORQUE TRANSMISSION









Accumulating Conveyor System

Nexen's CBU combined a tooth clutch interface with a friction brake interface to construct a clutch-brake with an integral double-single sprocket.

RESULT: Single piston configuration prevents clutch/brake overlap in an efficient design for nonslip performance even on heavy loads.

Additional Custom Product Examples:

- Multi-disc clutches in compact sizes for machines with space constraints
- Torque limiters to fit a drivetrain arrangement with a sensor for overload protection
- Clutch interfaces with ball/detents spaced for single and multiple positioning
- Spring-engaged units for specific holding torque and release pressure
- Unique drive flanges in a wide range of styles and diameters to fit all drive components
- IEC and NEMA flanged units designed to fit distinctly different sizes on the input and output ends
- Bore sizes, shaft sizes, bolt circles, and pilot diameters made to fit every motor up to 20 horsepower
- Corrosive resistant finishes to withstand severe environments
- · Units shortened or lengthened to fit a specific envelop

- Clutches with customer-specified integral sprockets and pulleys
- Caliper brakes designed for a wide variety of disc widths to absorb large amounts of heat energy
- Special machined involute splines with minimum backlash units for machine accuracy
- Air-engaged clutch combined with a spring-engaged brake having different input and output flanges
- Unique mounting adapter to mount a tension control brake on a specific manufacturer's roll stand
- Miniature clutch and control valve combination for cycle rates up to 300 cycles per minute
- Friction interfaces with special high torque and energy capacity material
- Brakes with unique bores for linear stage braking and holding



NEED HELP?

Contact Nexen's Custom Application Group: 800.843.7445 cbu@nexengroup.com



Nexen Group, Inc. 560 Oak Grove Parkway Vadnais Heights, MN 55127

800.843.7445 Fax: 651.286.1099 www.nexengroup.com